

# INDUCTION/INFRARED RANGE SERIES

Mantru.e

## 4-Burner Infrared Range



- Higher temperature, can reach 600 degree temperature.
- While reach 600 degree still can operate ceaseless.
- Can be suitable for different material cooker.

Model	ZT4-H9012A
Dimension(mm)	800x900x(810+120)
Rated Power(kw)	3x4
Rated Voltage	380V 3-phase 5-line



## Dual Burner Induction Range

Model	ZT2-C9007A
Dimension(mm)	450x900x(810+120)
Rated Power(kw)	3.5x2
Rated Voltage	380V 3-phase 5-line



## Dual Burner Infrared Range

Model	ZT2-H9006A
Dimension(mm)	450x900x(810+120)
Rated Power(kw)	3x2
Rated Voltage	380V 3-phase 5-line



## 4 Burner Induction Range

Model	ZT4-C9014A
Dimension(mm)	800x900x(810+120)
Rated Power(kw)	3.5x4
Rated Voltage	380V 3-phase 5-line



## 6 Burner Induction Range

Model	ZT6-C9021A
Dimension(mm)	1200x900x(810+120)
Rated Power(kw)	3.5x6
Rated Voltage	380V 3-phase 5-line



## 6 Burner Infrared Range

Model	ZT6-H9018A
Dimension(mm)	1200x900x(810+120)
Rated Power(kw)	3x6
Rated Voltage	380V 3-phase 5-line